



Order form
Purchaser

Valid from June 2016
Order no

Vaisala INTERCAP® Humidity and Temperature Probe HMP60

Vaisala INTERCAP® Humidity and Temperature Probe		HMP60															PRICE
1 Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4...20 mA converter (channel 1 only) Modbus RS485	A B C D I M R															
2 Measured parameter for channel 1	RS485 RH T (-40 ... +60°C) Td (-40 ... +60°C)	0 1 2 3															
3 Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +60°C) Td (-40 ... +60°C)	0 1 2 3															
4 Sensor protection	Plastic grid with filter Plastic grid Stainless steel sintered filter Catalytic filter 232637	A B C D															
5 Accessories	No accessories Pair of plastic nuts Duct installation kit 215619	0 1 3															
6 Humidity sensor	InterCap	A															
7 Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032 60 °C cable 3 m HMP50Z30A 180 °C FEP cable 3m 226902 180°C FEP cable 1.5m 238025	1 2 3 F J															
8 User guide	No user guide Multilingual quick guide	A B															
9 Loop power converter	No converter 4...20 mA loop power converter Always use single unit package	0 1 2															
TOTAL																	
QTY																	
TOTAL VALUE																	

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Example of order code with typical settings:

HMP60	A	1	2	A	0	A	1	B	0
-------	---	---	---	---	---	---	---	---	---